

# **Certificate of Compliance**

This certificate is issued for the following:

Polyethylene (PE) Pipe and Fittings for Underground Fire Protection Service

### **Friatec Fittings and Couplers**

(see details on following page)

### **Prepared for:**

Aliaxis Deutschland GmbH Steinzeugstr 50 Mannheim 68229 Germany

#### Manufactured at:

Aliaxis Deutschland GmbH Steinzeugstr 50 Mannheim 68229 Germany

FM Approvals Class: 1613 (February 2017)

Approval Identification: PR452814 Approval Granted: September 10, 2020

To verify the availability of the Approved product, please refer to www.approvalguide.com

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

David Fuller

VP - Manager of Fire Protection

FM Approvals

1151 Boston-Providence Turnpike

Norwood, MA 02062



Member of the FM Global Group



# **Certificate of Compliance**

Product Designation	Nominal Pipe Size, mm	Pressure Rating, psi (kPa)	Remarks
FRIALEN Slide-over Coupler (UB) SDR11	63, 75, 90, 110, 125, 140, 160, 180, 200, 225, 250, 280, 315, 355, 400, 450, 500	200 (1380)	а
FRIALEN Slide-over Coupler (UB) SDR9	400, 450, 500, 560, 630	250 (1725)	а
FRIALEN Slide-over Coupler (UB) SDR7.4	90, 110, 125, 140, 160, 180, 200, 225, 250, 315, 355	250 (1725)	а
FRIALEN Reducer (MR)	90x63, 110x63, 110x90, 125x90, 160x110, 225x160	200 (1380)	а
FRIALEN Elbow 30° (W30)	90, 110, 125, 140, 160, 180, 200, 225	200 (1380)	а
FRIALEN Elbow 45° (W45)	63, 75, 90, 110, 125, 140, 160, 180, 200, 225	200 (1380)	а
FRIALEN Elbow 90° (W90)	63, 75, 90, 110, 125, 140, 160, 180, 200, 225, 250, 280, 315	200 (1380)	а
FRIALEN Tee (T)	75, 90, 110, 125, 140, 160, 180, 200, 225, 250, 280, 315, 355, 400	200 (1380)	а
FRIALEN End Cap (MV)	63, 75, 90, 110, 125, 140, 160, 180, 200, 225	200 (1380)	а

#### Remarks

a. FRIALEN Fittings are electrofusion fittings designed to join two adjacent lengths of high density polyethylene pipe. The FRIAMAT family of fusion machines are used to fuse FRIALEN fittings to the pipe. Manufacturer's installation and assembly recommendations must be strictly followed for a proper joint.



Member of the FM Global Group